



AH9030

VIDEO CONFERENCE CAMERA



Technical Specifications

Full HD, Wide View Angle, Multiple Video Interfaces. Multiple protocols AH9030 series camera offers perfect functions, superior performance and rich interfaces. The features include advanced ISP processing algorithms to provide vivid images with a strong sense of depth, high resolution, and fantastic color rendition. It supports H.264/H.265 encoding which makes motion video fluent and clear even under less than ideal bandwidth conditions.

Model – AH9030			
View Angle	2.34° (Tele)-65.1°(Wide)	Iris/Electronic Shutter	Auto/Manual
Iris	F1.6 – F4.7 F =4.3~129mm	Focus	Auto/Manual
sensor	1/2.8 inch high quality HD	BLC	ON/OFF
	CMOS sensor	WDR	OFF/ Dynamic level adjustment
Effective Pixels	2.07MP,16: 9	Video Adjustment	Brightness, Color, Saturation, Contrast, Sharpness, B/W mode, Gamma curve
Optical Zoom	30X	SNR	>55dB
Digital Zoom	16X		
Minimum Illumination	0.5Lux (F1.8, AGC ON)		
DNR	2D&3D DNR		
White Balance	Auto/ Manual/ One Push/		
	3000K/3500K/4000K/4500K/		
	5000K/5500K/6000K/6500K/7K		
Video Interfaces	1x USB 3.0, 1x LAN, 1x RS485	Video Format USB3.0: 1920X1080P60/50/30/25, 1280X720P30/25115110, 960X540P30, 640X360P30,800X600P30 HDMI/HD Base video format; 1080P60150/30/25/59.94/29.97, 1080160/50/59.94,720P60/50130/25/59.94/29.97	
	1x HDMI, 1x 3G-SDI,1X3.5mm Jack		
Video Compression Format	H.264, H.265, Dual stream Output		
Control Protocol	VISCA/Pelco-D/Pelco-P		
	Baud Rate 115200/9600/4800/2400bps		
Resolution	Full HD		
Audio compression Format	AAC/MP3 Audio		
LAN Port	100M IP port (100BASE-TX), Support VISCA protocol control through IP port		
Network Protocol	RTSP, RTMP, ONVIF,		
	GB/T28181		
Power Interface	outlet (DC12V)		
Pan/Tilt Rotation	±170°, -30° +90°	Power Adapter	ACI 10V-AC220V to
Pan Control Speed	0.1~100°/sec		DCI2V/1.5A
Tilt Control Speed	0.1~45°/sec	Dimension	178mmX115.5mmX150.9mm
Preset Speed	Pan: 100°/sec, Tilt 45°/sec	Weight	1.38KG
Preset Number	255 presets (10 presets by remote controller)		

AVAILABLE THROUGH PAN INDIA DISTRIBUTOR & DEALER NETWORK

