




AS30


ACTIVE SPEAKER



Input sensitivity
0.7V



Frequency response
20Hz-20KHz/1 W, $\pm$ 0.5dB



Rated power
2 x 30W

Technical Specifications

- **Dynamic Sound:** Experience immersive audio with a pair of active wall speakers, featuring a powerful active speaker and a passive counterpart for balanced sound reproduction.
- **Built-in Amplification:** The active speaker comes equipped with a built-in amplifier, eliminating the need for external amplifiers and simplifying audio setup.
- **Expandable System:** Expand your sound system by adding additional passive speaker, creating a customized multi-room audio experience tailored to your preferences.
- **Easy Installation:** Designed for hassle-free setup, these speakers mount directly onto the wall, saving space while complementing any room decor.

Model	ATDSC AS30
Rated power	2 x 30W
Impedance	8 ohm
Input sensitivity	0.7V
Frequency response	20Hz-20KHz/1 W, ± 0.5dB
Total harmonic distortion	20Hz-20KHz/1 W, 0.05%
Damping factor	> 200 @ 8 Ω / 400Hz
Conversion rate	30V / US
Channel separation	>75 dB
SNR	>95 dB
Amplifier	AB class
Volume Control	Round Knob x 1
Treble Control	± 10 dB (Round Knob x1)
Bass Control	± 10 dB (Round Knob x1)
Input connections	Balanced Phoenix Terminal, 2 RCA unbalanced, Stereo 3.5mm Headphone Input
AC power supply	220V-240V/50Hz-60Hz
Speaker unit	6" woofer x 1, 1" tweeter x 1
Product dimensions	295 x 200 x 215mm
Net Weight	5.2KG/pair
Color	Black



AVAILABLE THROUGH PAN INDIA DISTRIBUTOR & DEALER NETWORK

